FOSTER HYDRAULICS

65 HP KUBOTA DIESEL
HYDRAULIC POWER UNITS

Heavy-duty Kubota diesel hydraulic power units for commercial, industrial and mobile applications. Standard fixed-displacement and pressure-compensated configurations provide 25-40 GPM with working pressures from 2,500 to 4,000 PSI.

65 HP	25-40 GPM	2,500-4,000 PSI	80 GAL.	25 GAL.
KUBOTA DIESEL	STANDARD FLOW	WORKING PRESSURE	HYD. RESERVOIR	FUEL TANK

FIXED DISPLACEMENT GEAR PUMP MODELS

Model	Pump	Flow	Pressure	Engine	Reservoir	Weight	Price
65K-1-25 D/C	Single Stage	25 GPM	4,000 PSI	69 HP*	80 gal.	3,050 lb.	$33,426
65K-1-30-D/C	Single Stage	30 GPM	3,500 PSI	69 HP*	80 gal.	3,050 lb.	$33,594
65K-1-35-D/C	Single Stage	35 GPM	3,000 PSI	69 HP*	80 gal.	3,050 lb.	$33,846
65K-1-40-D/C	Single Stage	40 GPM	2,500 PSI	69 HP*	80 gal.	3,050 lb.	$34,064

PRESSURE COMPENSATED PUMP MODELS

Model	Pump	Flow	Pressure	Engine	Reservoir	Weight	Price
65K-1P-25 D/C	Pressure Comp.	25 GPM	4,000 PSI	69 HP*	80 gal.	3,200 lb.	$35,426
65K-1P-30-D/C	Pressure Comp.	30 GPM	3,500 PSI	69 HP*	80 gal.	3,200 lb.	$36,594
65K-1P-35-D/C	Pressure Comp.	35 GPM	3,000 PSI	69 HP*	80 gal.	3,200 lb.	$36,594
65K-1P-40-D/C	Pressure Comp.	40 GPM	2,500 PSI	69 HP*	80 gal.	3,200 lb.	$36,594

STANDARD EQUIPMENT & PHYSICAL DATA

- 65 HP Kubota liquid-cooled diesel
- 4-stroke diesel power pack
- Direct fuel injection
- 25-gallon fuel tank
- Counter-balanced for high-speed operation
- 3-way, 2-position hydraulic selector valve
- Adjustable relief valve
- Liquid-filled pressure gauge
- 10-micron return-line filter
- Sight / level / temperature gauge
- Fan-cooled heat exchanger
- Adjustable thermostat
- Electric start with 12-volt battery and case
- Skid/platform with forklift access
- Quick couplers
- Dimensions: 50" x 82.5" x 63" tall
- 80-gallon hydraulic reservoir
- Single-stage pump; base page lists 25 GPM

FACTORY OPTIONS

Option	Description	Add
Protective Cage / Crane Lift	4-point overhead lifting / crane-lift provision	$2,075
Drip / Containment Pan	Containment pan for the power unit	$1,195
Installed Flow Meter	Factory-installed hydraulic flow meter	$995
Marine-Quality Powder Coat	Power unit	$995
Marine-Quality Powder Coat	Protective cage	$995

APPLICATIONS & CUSTOM CONFIGURATIONS

Typical applications: industrial hydraulic requirements, construction tools and equipment, utility installation and support, forestry, marine / ship-dock service, and agricultural requirements. **Additional configurations:** various control valves and activating controls, alternate pump types, trailer-mounted packages and larger reservoirs.

FOSTER MFG. CORP. / FOSTER HYDRAULICS
1836 Oakdale Ave., Racine, WI 53406 USA
262-633-7073
info@fostermfgcorp.com | FosterHydraulics.com

*The current product-family page is titled 65 HP, while its model table lists engine horsepower as 69 HP. The page also describes EPA Tier III compliance; Foster's newer technical guide describes the 65K-1-35 D/C with a Kubota V2403T, D.O.C. and Final Tier 4 certification. Confirm engine/emissions configuration when quoting. Pricing shown is from the current Foster Hydraulics 65 HP product-family page and is subject to change.